Accessories

D-sub-data transmission cord for AS-i Master in IP65, 1,5 m

AS-i Master in IP65 (Specification 2.0)

Clamps	PIN	Function	Colour
1		PE	
2		SHIELD	
3	3	BUS P	green
4	8	BUS N	yellow
5	5	GRND	blue
6		PE	
7		SHIELD	
8		BUS P	
9		BUS N	
10	6	+5 V	red

Article no. BW1097	
Connection	RS 485 prefabricated cable
Storage temperature	-40°C … +85°C
Operating temperature	-25°C … +60°C
Protection category (IEC) EN 60529	connector IP65, plug IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m

D-sub-data transmission cord 9-pin, 1,8 m

Article no. BW1058	
Connection	D-Sub plug D-Sub socket
Length	1,8m
PIN 1 connected with PIN 1	

D-sub-data transmission cord for AS-i Gateways with CAN interface

AS-i/CAN Gateway

Clamps	PIN	Function	Colour
1		n.c.	
2	7	CAN_H	white
3		SHIELD	
4	2	CAN_L	brown
5		n.c.	

Article no. BW1226	
Connection	D-subsocket, 5-pin COMBICON plug
Operating temperature	-40°C … +85°C
Storage temperature	-25°C … +60°C
Protection category (IEC) EN 60529	IP20
Dimensions (L, W, H)	ca. 50 mm, 20 mm, 30 mm
Length	1,5 m

Accessories

AS-i addressing cable (with COMBICON connector) for direct addressing with AS-i master

Article no. BW2324	
Connection	round connector 2-pin COMBICON-connector
Length	1,5 m
Connector (Master)	+ AS-i -

AS-i addressing cable - infrared addressing adapter

Article no. BW1935	
Connection	infrared head/M12 connector
Length	1 m

AS-i addressing cable for addressing with handheld address programming device

Article no. BW3304	
Connection	AS-i profile cable to M12
Length	1,0 m
scoop of delivery incl. 2 x substructure modules 60 mm x45 mm	

AS-i addressing cable for direct addressing with AS-i master

Article no. BW3305	
Connection	AS-i profile cable to COMBICON
Length	1,0 m
scoop of delivery incl. 2 x substructure modules 60 mm x45 mm	

Connecting cable (Module/programming device)

Article no. BW1802	
Connection	round connector 2-pin/ M12 connector
Length	1,6 m

Addressing plug

Article no. BW3340	
Colour	blue

Accessories

Protection cap for not used M12 sockets

Article no. BW2368	
Colour	blue
Packing unit	50 pieces

Memory plug cover

Article no. BW3155	
Colour	blue
Packing unit	1 piece

Cross-Link-cable for AS-i/Ethernet Gateway

Article no. BW1304

AS-i Probe

Article no. BW1745

Chip card for Bihl+Wiedemann AS-i products

Article no.	BW2079	BW2222
Memory capacity	32 kByte (256 kbit)	128 kByte (1024 kbit)
Labeling on the chip card	C 256	C 1024
Weight	approx. 1 g	
Dimensions (L / W / H in mm)	25 / 15 / 1	

Accessories:

- **BW2079** for all Standard and all Safety products with chip card by Bihl + Wiedemann.
- **BW2222** for Safety Monitors and Gateways in Stainless Steel Safety Version 4.X (for maximum 4 Safety configurations on a chip card).