Product data sheet
Characteristics

ASISEA1C
AS-Interface - premounted in emergency stop station XALK - turn to release

Main

Product or component type	Interface premounted in emergency stop station XALK
Range compatibility	AS-Interface cabling system
Type of operator	Turn to release
Number of contacts	2
AS-i profile	0.B.F.F
Supply	Via AS-Interface

Complementary

Addressing	Using adjustment terminal
[Us] rated supply voltage	24 V DC (- 15...15 %)
Power consumption	1.2 W
Current consumption	45 mA for AS-Interface line
Connections - terminals	1 connector M12 for AS-Interface line
Mechanical durability	300000 cycles
Product weight	0.17 kg

Environment

Standards	EN/IEC 60204-1 EN/IEC 60947-5-3 EN/IEC 61496-1 EN/ISO 12100 EN/ISO 13850 EN 1088/ISO 14119 EN 954-1 category 4 ISO 13849-1 category 4
Product certifications	CSA UL
IP degree of protection	IP65 conforming to IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C
Vibration resistance	5 gn
Shock resistance	10 gn
RoHS EUR conformity date	0632
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.